



Key Features

- Through-the-wall installation
- Quiet and efficient operation
- Advanced electronic control system
- Liquid-temperature-measuring bottle probe
- Can be mounted above the door
- 30°F temperature differential

Features

The Slimline is WhisperKOOL's quietest interior-venting, self-contained unit available, developed to fit into the often unused space between the cellar door and ceiling. This gives the collector maximum storage capacity. The system is equipped with WhisperKOOL's Platinum Series controller utilizing Advanced System Protection Technology. This features a series of strategically placed monitoring probes, which insure efficient performance and long cooling unit life. With efficiency in mind, the Slimline uses less power than most traditional units while having the ability to cool cellars up to 300 cu. ft. and 650 cu. ft.

Specifications

Model	2500	3300
Cellar Size	300 cu. ft.*	650 cu. ft.*
BTU/h (85°F condenser air intake temperature)	1453	2049
CFM	94	126
Dimensions	19"L x 22"W x 10.25"H	
Refrigerant	R-134a	
HP	0.57	0.8
Voltage Rating	115V (20 amp dedicated circuit required); 230V (subject to availability)	
Weight (lbs)	60	60
Amps	3.5 (running amps)	
Drain Line	3/8" ID clear plastic tubing (not provided)	
Installation	Through the wall, ideally above a doorway	
Thermostat	Advanced digital display, liquid-temperature-measuring bottle probe (retractable cable)	
Temp. Delta	Can maintain a 55°F cellar temperature with up to 85°F condenser air intake temperature	
Warranty	Two-year limited warranty (parts and labor) / Five-year limited warranty (compressor)	

*Approximated in an environment that is fully insulated and sealed with a proper vapor barrier. Each wine cellar is unique and has specific cooling requirements. Heat load calculations should always be performed prior to selecting a cooling unit.

